

STORM

Bottom-Loading Bottled Water Cooler



Healthy, Stylish and Ergonomic

- Award winning contemporary design
- Appliance look with high gloss finish
- Space-saving front door, slides upward
- SmartFlo SF-1 water cartridge allows for easy sanitization
- Less handling of bottles
- Higher dispense point
- Taller dispensing area – fits sports bottles
- Enhanced customer experience
- Recessed water outlet—more hygienic
- LED lit faucet area
- Low water level indicator
- Exceeds new, lower Energy Star standards
- Holds 3, 4, and 5-Gallon bottles



Bottle in the bottom



SmartFlo SF-1 Water Cartridge:

The most convenient and efficient way to thoroughly sanitize your water dispenser. All of the water contact components are removed and replaced with a new sanitary system. Your water cooler can be easily and fully sanitized in minutes.

STORM

Technical Data & Specifications

Cooler Cabinet: Black ABS cabinetry with stainless look accessories. Space-saving front door slides up rather than swinging open.

Faucet Type: Covered mechanical style faucet system with replaceable water contact components (via SmartFlo SF-1 water cartridge) and a recessed dispensing point to protect from contamination are durable and add to the stylish presentation.

Cold Water Reservoir: SmartFlo SF-1 water cartridge casing with 1.6L (.4 gal) volume. Cold water cooling capacity of 2.8L/hr (.7 gal/hr) at a 21°C (70°F) room temperature.



Cold Water Thermostat: Temperature can be adjusted by an easily accessed control on the rear of the cabinet. Adjustable range from 39-50°F (4-10°C).

Hot Water Tank: One piece tank made of 304 stainless steel with 1.1L (0.3 gal) volume. Hot water capacity of 1.45 gal/hr (5.5 L/hr) at a 70 °F (21°C) room temperature.

Hot Water Thermostat and Heater: Automatic thermostat set at a temperature range of 169-198°F (76-92°C) with safety limiter.

Energy Star Certified: 0.70 kwh/day, exceeds new EPA standard of 0.87 kwh/day.

Hot Water Capacity: 1.45 gal/hr based upon a 21°C (70°F) room temperature.

Compressor: Hermetically sealed reciprocating compressor (100-110 VAC, 60 Hz).

Refrigerant Type: R134a

Refrigerant Charge: 35g (1.2 oz)

Noise Level:

Pump: 55dB

Compressor: 43dB

Warranty: Limited one year warranty. One year on the sealed refrigeration system and most component parts.

Dimensions & Freight Data:

Product Dimensions: 43.9" (1116mm) H x 12.6" (320mm) W x 13.4" (340mm) D

Product Weight: 32 lbs (14.5 kg)

Product Boxed Dimensions: 45.9" (1165mm) H x 13.4" (340mm) W x 15" (380mm) D

Product Boxed Weight: 35.7 lbs (16.2 kg)



Crystal Mountain Products Limited · 11925 -145st NW · Edmonton AB T5L 2H4
sales@crystalcoolers.com · 800-878-6422 · 780-454-9816 (fax) · www.crystalcoolers.com

Crystal Mountain has a policy of continuous development and reserves the right to change specifications without notice.

©2013, Crystal Mountain Products Limited